







Optionale Rollen für Pflegebett 5384 Kepler (Zusatz für die Gebrauchsanweisung G153)

Für das Pflegebett 5384 Kepler werden folgende Rollen optional angeboten:







Artikel Nr.	Baugruppe	Bauteile	Durchmesser Rolle	Liegefläche erhöht sich auf	
BG6081	Linea 	① 1 x R2095 - Richtungsfeststeller - elektrisch leitfähig ② 2 x R2071 - Totalfeststeller ③ 1 x R2070 - Totalfeststeller - elektrisch leitfähig	125,0 mm	278,0 - 830,0 mm (Bauhöhe: 130,0 mm)	
BG6291	Integral S 	① 2 x R2125 - Totalfeststeller ② 1 x R2126 - Totalfeststeller - elektrisch leitfähig ③ 1 x R2127 - Richtungsfeststeller - elektrisch leitfähig	125,0 mm	306,0 - 858,0 mm (Bauhöhe: 158,0 mm)	
BG5264	Integral S 	① 1 x R2064 - Totalfeststeller - elektrisch leitfähig ② 2 x R2065 - Totalfeststeller ③ 1 x R2107 - Richtungsfeststeller - elektrisch leitfähig	150,0 mm	331,0 - 883,0 mm (Bauhöhe: 183,0 mm)	

Artikel Nr.	Baugruppe	Bauteile	Durchmesser Rolle	Bauhöhe	Liegefläche erhöht sich auf
R2071	Linea	4 x R2071	125,0 mm	130,0 mm	278,0 - 830,0 mm
R2125	Integral S	4 x R2125	125,0 mm	158,0 mm	306,0 - 858,0 mm
R2065	Integral S	4 x R2065	150,0 mm	183,0 mm	331,0 - 883,0 mm
R2115	Steinco (Standard Modell Select rangierbar)	4 x R2115	100,0 mm	115,8 mm	---

Diese Rollensätze bestehen aus jeweils vier gleichen Rollen!

Optional castors for 5384 Kepler bed (supplement to user manual G155)

The following optional castors are available for the 5384 Kepler bed:

Item no.	Assembly	Components	Castor diameter	Height of bed surface increased to	
BG6081	Linea 	<ul style="list-style-type: none"> ① 1 x R2095 - Directional device - Electrically conductive ② 2 x R2071 - Locking devices ③ 1 x R2070 - Locking device - Electrically conductive 	125.0 mm	278.0 - 830.0 mm (Construction height: 130.0 mm)	
BG6291	Integral S 	<ul style="list-style-type: none"> ① 2 x R2125 - Locking device ② 1 x R2126 - Locking device - Electrically conductive ③ 1 x R2127 - Directional device - Electrically conductive 	125.0 mm	306.0 - 858.0 mm (Construction height: 158.0 mm)	
BG5264	Integral S 	<ul style="list-style-type: none"> ① 1 x R2064 - Locking device - Electrically conductive ② 2 x R2065 Locking devices ③ 1 x R2107 - Directional device - Electrically conductive 	150.0 mm	331.0 - 883.0 mm (Construction height: 183.0 mm)	

Item no.	Assembly	Components	Castor diameter	Construction height	Height of bed surface increased to
R2071	Linea	4 x R2071	125.0 mm	130.0 mm	278.0 - 830.0 mm
R2125	Integral S	4 x R2125	125.0 mm	158.0 mm	306.0 - 858.0 mm
R2065	Integral S	4 x R2065	150.0 mm	183.0 mm	331.0 - 883.0 mm
R2115	Steinco (manoeuvrable, standard model Select)	4 x R2115	100.0 mm	115.8 mm	---

These sets of castors each consist of four identical castors!